

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028971 A1**

(51) International Patent Classification<sup>7</sup>: **F25B 40/00**,  
41/06

(21) International Application Number:  
PCT/DK2004/000611

(22) International Filing Date:  
16 September 2004 (16.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PA 2003 01374 22 September 2003 (22.09.2003) DK

(71) Applicant and

(72) Inventor: **ZIMMERMANN, Lars, Christian, Wulff**  
[DK/DK]; Hoejgaardsparken 18, DK-8380 Trige (DK).

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

(54) Title: CIRCUIT WITH TWO-STEP CAPILLARY TUBE THROTTLING AND RECEIVER



(57) Abstract: A Thermostatic Flow Controller composed of two capillary tubes and a tube form receiver, placed in thermal contact with the suction line. It makes a robust, hermetic closed device, without any moveable parts, no need for adjustment or service and therefor suited for inaccessible placement - for instance encapsulated in isolation foam. The flow of refrigerant to the evaporator is controlled by the pressure in the receiver - and the pressure in the receiver is controlled by the need for refrigerant in the evaporator. This balance ensures that the evaporator is flooded, and thereby exploited 100% - for all kind of charges. The invention is suited for small household freezers and refrigerators. For a small extra cost, it replaces the traditional capillary tube, and makes these devices working optimal on both cold and warm locations, and makes the manufacturing more easy because the amount of refrigerant is no longer critical as it is for traditional capillary tubes.

WO 2005/028971 A1